

**DECLARATION OF PERFORMANCE**  
**In accordance with annex III of Regulation (EU) 305/2011**

**Name of the product**  
**ISOMAT AK-20 WHITE**  
**No. 08/EN 12004:2007 + A1:2012/01/25-07-13**

1. Unique identification code of the product-type:	<b>ISOMAT AK-20 WHITE Tile Adhesive</b>
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):	<b>See batch number and date of manufacture on packaging</b>
3. Intended use or users of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:	<b>Normal setting cementitious adhesive Type C2 intended for internal and external floor or wall finishes</b>
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11(5):	<b>ISOMAT S.A. 17<sup>th</sup> Km Thessaloniki-Ag. Athanasios 57003 Ag. Athanasios Greece</b>
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):	<b>Not applicable</b>
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:	<b>System 3</b>
7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:	<b>The notified body BUILDING RESEARCH INSTITUTE (NISI) Ltd. Identification NB 2032 has carried out initial type testing to system 3 and issued Test report No. ITT-10.13/12.10.2012</b>

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:	<b>Not applicable</b>
---	-----------------------

9. Declared performance

Essential characteristics	Performance	Test Standard	Harmonized technical specification
Initial tensile adhesion strength	$\geq 1.0 \text{ N/mm}^2$	EN 1348:2007 (8.2)	EN 12004:2007 +A1:2012
Tensile adhesion strength after water immersion	$\geq 1.0 \text{ N/mm}^2$	EN 1348:2007 (8.3)	
Tensile adhesion strength after heat ageing	$\geq 1.0 \text{ N/mm}^2$	EN 1348:2007 (8.4)	
Tensile adhesion strength after freeze-thaw cycles	$\geq 1.0 \text{ N/mm}^2$	EN 1348:2007 (8.5)	
Open time: tensile adhesion strength after not less than 30min	$\geq 0.5 \text{ N/mm}^2$	EN 1346:2007	
Reaction to fire	Class A1	EN 13501-1	

10. Declaration	The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. this declaration of performance is issued under the sole responsibility of the manufactured identified in point 4.
-----------------	---

Signed for and on behalf of the manufacturer by:



Kostantinos Iliopoulos  
Quality manager



Samaras Thomas  
R & D manager