

## DECLARATION OF PERFORMANCE

according Annex III of the Regulation (EU) No 305/2011

Name of the product

### **MARMOCRET PLUS DECOR**

No. 06/EN 998-1/01/08-07-13

1. Unique identification code of the product-type:  
**MARMOCRET PLUS DÉCOR**
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):  
**batch number: see packaging of the product**
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:  
**General purpose mortar (GP) polymer modified for coarse textured finish**
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):  
**ISOMAT S.A**  
**17th Km Thessaloniki-Ag. Athanasios 57003**  
**Ag. Athanasios, Greece**
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):  
**not relevant**
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:  
**System 4 (Factory made rendering/plastering mortars)**
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:  
**not relevant**
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:  
**not relevant**

9. Declared performance

Essential characteristics	Performance	Test Method	Harmonised Technical specification
Compressive strength	CS II	EN 1015-11	EN 998-1:2010
Reaction to fire	class A1	EN 13501-1	
Capillary water absorption	W2	EN 1015-18	
Water vapor permeability	5/20 (tabulated value)	EN 1745	
Adhesion	$\geq 0,7 \text{ N/mm}^2$ (FP:B)	EN 1015-12	
Thermal conductivity $\lambda_{10 \text{ dry}}$	0,47 (W/mK) (tabulated value)	EN 1745	
Durability	evaluation based on provisions valid in the intended place of use of the mortar		

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



.....  
**Konstantinos Iliopoulos**  
 Quality manager



.....  
**Panagiotis Avramidis**  
 R&D manager

**Agios Athanasios 08/07/2013**